

DeWitt Company, Inc.

Nonwoven Geotextile 120

Specification Sheet

DeWitt Item Numbers		FF145 - 12.5360 FF145 -15300
Sizes Available		12.5' x 360' (500 yd ²) 15' x 300' (500 yd ²)
Roll Weight		152 / 180 lbs
Primary Applications		Separation, Drainage Asphalt Overlay
Grab Tensile(lbs)	ASTM D-4632	120
Elongation (%)	ASTM D-4632	50
Trapezoid Tear (lbs)	ASTM D-4533	50
Puncture Resistance (lbs)	ASTM D-4833	70
UV Stability (% @ 500 hrs)	ASTM D-4355	70
Permittivity (sec ⁻¹)	ASTM D-4491	1.8
Flow Rate (gpm/ft ²)	ASTM D-4491	120
A.O.S (US Sieve #)	ASTM D-4751	70
Weight (oz/yd ²)	ASTM D-5261	4.5
Mullen Burst(psi)	ASTM D-3786	225

Date: 09/01/2011. This data sheet supersedes all previously issued data sheets.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled, however, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information nor do we offer any warranty against patent infringement.