

DeWitt Company, Inc.
6 oz Needlepunch Nonwoven Pond Underliner
(50/50 Polypropylene / Polyester)

<u>Property</u>	<u>Test Procedure</u>	
<u>Properties</u>	<u>Test Method</u>	
Tensile Strength (lbs)	ASTM D-4595	325
Elongation (%)	ASTM D-4595	35
Trapezoid Tear (lbs)	ASTM D-4533	50
Puncture (lbs)	ASTM D-4833	80
A.O.S. (U.S. sieve no.)	ASTM D-4751	100
Weight (oz/yd ²)	ASTM D-5261	6
Polymer Composition	50% Polypropylene 50% Recycled Polyester	

Date: 01/01/2011. This data sheet supersedes all previously issued data.
The above properties are typical averages.

THIS INFORMATION RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS, SUCH INFORMATION IS TO THE BEST OF OUR KNOWLEDGE AND BELIEF, ACCURATE AND RELIABLE AS THE DATE COMPLIED. HOWEVER NO REPRESENTATION, WARRANTY OR GUARANTEE IS MADE AS TO ITS ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY HIMSELF AS TO THE SUITABILITY AND COMPLETENESS OF SUCH INFORMATION FOR HIS OWN PARTICULAR USE. WE DO NOT ACCEPT LIABILITY FOR ANY LOSS OR DAMAGE THAT MAY OCCUR FROM THE USE OF THIS INFORMATION NOR DO WE OFFER ANY WARRANTY AGAINST PATENT INFRINGEMENT.