

DeWitt Company, Inc.
Nonwoven Geotextile 205
Specification Sheet
(Compare to Terratex NO8)

DeWitt Item Number		DNG205 -15300
Size Available		15' x 300' (500 yd ²)
Roll Weight		290 lbs
Primary Applications		Stabilization Permanent Erosion Control
Grab Tensile(lbs)	ASTM D-4632	205
Elongation (%)	ASTM D-4632	50
Trapezoid Tear (lbs)	ASTM D-4533	85
Puncture (lbs)	ASTM D-4833	130
UV Stability (% @ 500 hrs)	ASTM D-4355	70
Permittivity (sec ⁻¹)	ASTM D-4491	1.4
Flow Rate (gpm/ft ²)	ASTM D-4491	90
A.O.S (US Sieve #)	ASTM D-4751	80
Weight (oz/yd ²)	ASTM D-5261	8

Date: 09/11/2011. This data sheet supersedes all previously issued data sheets.
This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled, however, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information nor do we offer any warranty against patent infringement.