

DEWITT COMPANY, INC
POLYESTER THREAD SPECIFICATIONS

CONSTRUCTION	MULTIFILAMENT POLYESTER
DENIER SIZE	1096
STRENGTH: SINGLE-END BREAK	13.31 LBS
ELONGATION: ELONGATION AT BREAK	18.07%
SHRINKAGE: BOILING WATER HOT AIR	<2% <3%
LOOP STRENGTH RATIO	16.73
SEAM STRENGTH: 301SSA-1 LOCKSTITCH (8SPI) 401SSA=1 CHAINSTITCH (8 SPI)	157.0 178.0

ADVANTAGES:

SUPERIOR STRENGTH
ULTRA-VIOLET LIGHT RESISTANCE
(PRE-DYED FIBRES OFFERS EXCELLENT RETENTION IN SUNLIGHT)
VERY GOOD SEAM STRENGTH
EXCELLENT ABRASION RESISTANCE
TWISTED MULTIFILAMENT BONDED THREADS HAVE SUPERIOR PLY SECURITY

Date: 04/05/2011. This data sheet supersedes all previously issued data sheets.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled, however, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information nor do we offer any warranty against patent infringement.