

DeWitt Company, Inc. **Zip Tie Specification**

Material		Nylon 6/6 UV Stabilized
Continuous Operating Temperature		Max: 185°F 85°C Min: -40° -40°C
Tensile Strength at 73°F Dry as molded	ASTM-D-638	12000 (PSI)
UL Flame Rating		94V-2
Oxygen Index %		N/A
Gamma Radiation Resistance		1 X 10 Rads
UV Resistance		Very Good
Military, Federal and ASTM Specifications		ASTM-D4066 PA181

UV Stabilized Nylon 6/6 is used in continuous or extended exposure to outdoor sunlight. The nylon cable is a weather resistant grade, enduring additional ultraviolet (UV) light. Incorporating stabilizers in the nylon resin produces this grade. UV Stabilized Nylon cable ties are only available in black.

Date: 03/24/2006. This data sheet supersedes all previously issued data.
The above properties are typical averages.

THIS INFORMATION RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS, SUCH INFORMATION IS TO THE BEST OF OUR KNOWLEDGE AND BELIEF, ACCURATE AND RELIABLE AS THE DATE COMPLIED. HOWEVER NO REPRESENTATION, WARRANTY OR GUARANTEE IS MADE AS TO ITS ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY HIMSELF AS TO THE SUITABILITY AND COMPLETENESS OF SUCH INFORMATION FOR HIS OWN PARTICULAR USE. WE DO NOT ACCEPT LIABILITY FOR ANY LOSS OR DAMAGE THAT MAY OCCUR FROM THE USE OF THIS INFORMATION NOR DO WE OFFER ANY WARRANTY AGAINST PATENT INFRINGEMENT.