



**(RWB)**  
**REFLECTIVE WHITE/BLACK GROUND COVER**

PROPERTY	Units	TYPICAL AVERAGE VALUE (MD/CMD)
<b>MECHANICAL</b>	-	-
Grab Tensile Strength (ASTM D4632)	Lbs	140 / 150
Grab Elongation (ASTM D4632)	%	25 / 22
Trapezoidal Tear Strength (ASTM D4533)	Lbs	85 / 85
Static Puncture Strength (ASTM D6241)	Lbs	600
<b>ENDURANCE</b>	-	-
UV Resistance (ASTM D6241) @ 2500 Hrs	%	70
<b>HYDRAULIC</b>	-	-
Water Flow Rate (ASTM D4491)	Gal/Min/ft	50
<b>PHYSICAL</b>	-	-
Mass Per Unit Area (ASTM D5261)	Oz/yd	3.8
Mesh Count	Per/Inch	20 X 12.5
Color	-	Black & White Two Way

Date: 9/28/18. This data sheet supersedes all previously issued data. The above properties are typical averages.

THIS INFORMATION RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS, SUCH INFORMATION IS TO THE BEST OF OUR KNOWLEDGE AND BELIEF, ACCURATE AND RELIABLE AS THE DATE COMPLIED. HOWEVER NO REPRESENTATION, WARRANTY OR GUARANTEE IS MADE AS TO ITS ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY HIMSELF AS TO THE SUITABILITY AND COMPLETENESS OF SUCH INFORMATION FOR HIS OWN PARTICULAR USE. WE DO NOT ACCEPT LIABILITY FOR ANY LOSS OR DAMAGE THAT MAY OCCUR FROM THE USE OF THIS INFORMATION NOR DO WE OFFER ANY WARRANTY AGAINST PATENT INFRINGEMENT.

---

**905 South Kingshighway Sikeston, MO 63801 / [www.dewittcompany.com](http://www.dewittcompany.com)**  
**573.472.0048 phone / 800.888.9669 / 573.471.6715 fax**

