DeWitt
DOWN TO EARTH PROTECTION

Product Specification Sheet

Zip Ties

DeWitt Zip Ties UV stabilized nylon 6/6 is used in continuous or extended exposure to outdoor exposure. The nylon cable is a weather resistant grade, enduring additional ultraviolet (UV) light. Incorporating stabilizers in the nylon resin produces this grade. UV Stabilized Nylon cable ties are only available in black.

Material	Nylon 6/6 UV Stabilized
Continuous Operating Temperature	Max: 185F 85C Min: -40 -40C
Tensile Strength at 73F Dry as Molded	ASTM-D-638 12000 (PSI)
UL Flame Rating	94V-2
Oxygen Index %	N/A
Gamma Radiation Resistance	1 x 10 Rads
UV Resistance	Very Good
Military, Federal and ASTM Specifications	ASTM-D4066 PA181

*At the time of manufacturing. Handling may change these properties

Date: 06/01/23. This data sheet supersedes all previously issued data.
The above properties are typical averages.

THIS INFORMATION RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS, SUCH INFORMATION IS TO THE BEST OF OUR KNOWLEDGE AND BELIEF, ACCURATE AND RELIABLE AS THE DATE COMPLIED. HOWEVER NO REPRESENTATION, WARRANTY OR GUARANTEE IS MADE AS TO ITS ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILTY TO SATISIFY HIMSELF AS TO THE SUITABILITY AND COMPLETENESS OF SUCH INFORMATION FOR HIS OWN PARTICULAR USE. WE DO NOT ACCEPT LIABILITY FOR ANY LOSS OR DAMAGE THAT MAY OCCUR FROM THE USE OF THIS INFORMATION NOR DO WE OFFER ANY WARRANTY AGAINST PATENT INFRINGEMENT.

905 South Kingshighway Sikeston, MO 63801
573.472.0048 phone • 800.888.9669 • 573.471.6715 fax • dewittcompany.com

DeWitt
DOWN TO EARTH PROTECTION